Appl. No. 10/059,700 Reply to Examiner's Action dated June 3, 2005

IN THE CLAIMS:

1. (Currently Amended) A method of manufacturing piezoelectric wafers of surface acoustic wave (SAW) identification tags, comprising:

using a master reticle on a stepper to form, on each of said piezoelectric wafers, wafer-independent patterns that encode digits of a first significance for said SAW identification tags; and using different ones of a library of coding reticles on a stepper to form, on each of said piezoelectric wafers, wafer-dependent patterns that encode digits of a second significance for said SAW identification tags.

- 2. (Original) The method as recited in Claim 1, further comprising forming a SAW transducer on each of said SAW identification tags.
- 3. (Currently Amended) <u>A method of manufacturing piezoelectric wafers of surface acoustic</u> wave (SAW) identification tags, comprising:

using a master reticle to form, on each of said piezoelectric wafers, wafer-independent patterns that encode digits of the first significance for said SAW identification tags; and

using different ones of a library of coding reticles to form, on each of said piezoelectric wafers, wafer-dependent patterns that encode digits of the second significance for said SAW identification tags. The method as recited in Claim 1, further comprising forming said wafer-independent and wafer-dependent patterns by forming composed of reflectors distributed among a group of slots arranged by both pulse position and by phase position, said reflectors encoding said digits of a the first significance and said digits of a the second significance.

4. (Original) The method as recited in Claim 3 wherein said reflectors are structures that

DEC. 5. 2005 11:33AM HITT GAINES 9724808865 NO. 3021

P. 7

Appl. No. 10/059,700 Reply to Examiner's Action dated June 3, 2005

reflect a surface acoustic wave.

5. (Original) The method as recited in Claim 3 further comprising forming a framing

reflector on said SAW identification tags, said framing reflector located between said SAW

transducer and said group of slots.

6. (Original) The method as recited in Claim 3 further comprising forming a plurality of said

groups separated by dead spaces.

7. (Original) The method as recited in Claim 6 wherein said plurality of groups is at least

twelve.

8. (Original) The method as recited in Claim 4 wherein at least some of said reflectors are

single strips of conductive metal.

9. (Original) The method as recited in Claim 3 further comprising forming an end reflector

on said SAW identification tags.

Claims 10-31 (Canceled)

6